

AKVATERM ACCUMULATOR TANKS

Capacity 300-10,000 litres. The insulation is 100 mm seamless polyurethane faced with steel sheet. Detachable side panels are also an option. The upper hatch has a standard hot water coil. A domestic hot water pre-heating coil, a solar heating coil and other coils can be placed in the lower hatch. There are 2" couplings for the electrical resistors located at centre and bottom of the tank. Built-in guide pipes ensure the proper layering of heat. Standard domestic hot water coil size LK35. Standard pressure class 1.5 bar. Other available pressure classes 3, 4 and 6 bar.



MODEL	DIAMETER mm	HEIGHT mm	WEIGHT kg	CONNECTIONS SIZE (ID 2/5)	RESISTOR COUPLINGS
AKVA 750 EK	950	2050	200	1 1/4 "	2
AKVA 1000 EK	1050	2100	230	1 1/4 "	2
AKVA 1500 EK	1250	2150	280	1 1/4 "	3
AKVA 2000 EK	1400	2200	330	1 1/4 "	4
AKVA 2500 EK	1500	2250	360	1 1/4 "	4
AKVA 3000 EK	1600	2300	400	1 1/4 "	4
AKVA 4000 EK	1800	2450	480	1 1/4 "	6
AKVA 5000 EK	2000	2500	600	2 "	6